



U2 SmartONE

THE ONE & ONLY

Introducing U2-SmartONE™
the world's first ONE inch TIJ printer
ONLY at ANSER



0.5-inch 1-inch

1. Solid 1-inch cartridge, specially designed for industrial coding market
2. No stitching required, with seamless print quality for higher readable rate
3. Compact-sized for easy installation and system integration

U2 SmartONE™
you too, SmartONE



Actual Print Size

Solid 1-inch Cartridge



Stitching Cartridge



U2-SmartONE™ Features:



High Readable Rate Barcodes
Capable of printing crispy 1D & 2D barcodes including EAN 128, Code 128, Code 39, Datamatrix, QR and etc.



Zero-Maintenance
The ink cartridge design eliminates unnecessary printhead services; it is truly zero-maintenance and has drastically decreased your total cost of ownership.



Pocket-sized Remote Keypad
Handy and compact remote keypad with comprehensible design for easy operation.



Friendly UI & Intelligent Dashboard
Simple yet elegant user interface for easy operation. The intelligent dashboard design monitors the printer status and provides real-time system notifications.



Automatic Ink Identification
Automatically identifies and selects the proper firing parameter to ensure the best print quality.



Anti-Shock Mechanism Design
Anti-Shock Mechanism Design eliminates the unexpected damage to your printer with ANSER's unique protective design.

U2-SmartONE™ Specifications:

Display	3.5" Color LCD with LED backlight
User-interface	Simple and easy-to-use operating system
Input Device	Pocket-sized IR remote keypad
Available Languages	English, Japanese, French, German, Spanish, Portuguese, Russian, Korean, Italian, Turkish, Hungarian, Slovak, Czech, Swedish, Romanian, Serbian, Bulgarian, Chinese (Traditional & Simplified), Polish, Farsi, Arabic
LED Indicators	Alarm, Ink Low, Print, Run, Remote on/off
Print Engine	Thermal Ink Jet Technology
Print Resolution & Print Speed	300 dpi (60m/min) Print quality is resolution & speed dependent.
Print Distance	Max 6mm
Print Height	Up to 25.4mm(1-inch). Selectable font size: 5.4mm, 7.2mm, 11mm, 16mm, 20mm, 25.4mm
Print Capability	Alphanumeric, logos, date/time, shift code, counter, lot box code
Barcodes	EAN8, EAN13, EAN14, EAN128, UPCE, CODE39, CODE128, TF14 (SCC-14), NVE18 (SSCC-18), C25INTER, CODABAR, PDF417, DATAMATRIX, QR CODE
Power Adapter	Input AC 100V~240V, 50/60Hz Output DC 12V/5A, 60W
Weight	0.49kg (1.08 lb.) - excluding cartridge and bracket
Dimensions (L/W/H)	114x76x60 (mm)
Mounting Orientation	Horizontal or downside
Message Storage Capacity	Store up to 999 messages
Operating Temperature	5°C – 40°C (41°F – 104°F)
Data Interface	RS485 & USB Host

Optional Accessories:

Encoder	Provide high print quality on unstable conveyor
Photocell	Provide more reliable and precise sensing parameter
Alarm Kit	Alert users in the event of an incident



WWW.ANSER-U2.COM



ANSER CODING INC.



FELIX
SOLUTIONS

Unit No 2, 1st Floor, Gami Industrial Park,
Plot No. C-39A, TTC Industrial Area, Pawane MIDC,
Navi Mumbai - 400705, Maharashtra, India
Mob: 9664359927, 9870610432
Email: felixsolutions1@gmail.com
Web: www.felixsolutions.in

www.felixsolutions.in